

SHUTTLE 2

ELECTRIC OR
GAS POWERED
CARGO CARRIER

13 hp Kawasaki® Gas Engine or
48-volt Electric Drivetrain
20.9-sq ft. cargo deck



Features and specifications of vehicles subject to change without notice.
Vehicle as photographed may include options not included on base model.



CUSHMAN



Delivers More than Hard Work

When you need to move a lot of large material around your facility in a hurry, the Cushman Shuttle 2 is the right choice. With a 1,200-pound cargo capacity and a 20.9-square-foot cargo deck, the Shuttle 2 can move anything from lumber to luggage. And whether it's equipped with a 48-volt DC electric drivetrain or a 13 hp Kawasaki® gas engine, the Shuttle 2 offers plenty of power to get the job done right. An optional limited-slip differential helps maintain traction and control on wet surfaces for maximum safety and performance.



SHUTTLE 2 ELECTRIC AND GAS CARGO CARRIER

	ELECTRIC	GAS
DIMENSIONS		
Overall Length	141.0 in (358 cm)	141.0 in (358 cm)
Overall Width	48.5 in (123 cm)	48.5 in (123 cm)
Overall Height w/o Roof	48.6 in (123 cm)	48.6 in (123 cm)
Overall Height w/ Struts & Roof	72.0 in (183 cm)	72.0 in (183 cm)
Wheel Base	93.5 in (237 cm)	93.5 in (237 cm)
Front Wheel Track	34.2 in (85 cm)	34.2 in (89 cm)
Rear Wheel Track	38.0 in (97 cm)	38.0 in (97 cm)
Ground Clearance	4.3 in (11 cm)	4.75 in (12 cm)
Cargo Bed Width (inside)	44 in (112 cm)	44 in (112 cm)
Cargo Bed Length (inside)	68.5 in (174 cm)	68.5 in (174 cm)
Cargo Deck Capacity	20.9 sq ft (1.94 m ²)	20.9 sq ft (1.94 m ²)
POWER		
Power Source	48V DC	4-Cycle, 24.5 ci (401cc) Low Emission
Motor Type/Valve Train	Shunt Wound	Single Cylinder OHV
Horsepower (kW)	18.1 hp (13.5 kW) @ 1900 rpm	13 hp (9.7 kW) Exceeds SAE J1940 Std.
Electrical System	48V	Starter/Generator. Solid State Reg.
Batteries (Qty, Type)	Eight, 6V Deep Cycle	One, 12V Maintenance Free
Drive Train	Motor Shaft Direct Drive	Continuously Variable Transmission
Oil Filter	n/a	Spin-On
Cooling System	n/a	Air Cooled
Fuel Capacity	n/a	5.8 Gallon (22.0 L) Tank
Gear Selection	Dash Mount F-N-R Switch	Forward - Reverse
Transaxle	Differential with Helical Gears	Differential with Helical Gears
Rear Axle Ratio	14.7:1	11.42:1(Forward) 15.78:1(Reverse)
PERFORMANCE		
Seating Capacity & Style	2-Person	2-Person
Dry Weight	720 lb (325 kg)	851 lb (385 kg)
Curb Weight (w/ batteries)	1210 lb (550 kg)	891 lb (405 kg)
Vehicle Load Capacity	1000 lb (450 kg)	1200 lb (545 kg)
Outside Clearance Circle	25.5 ft (7.8 m)	25.5 ft (7.8 m)
Speed (level ground)	13 mph +/- 0.5 mph (21 kph +/- 0.8 kph)	16 mph +/- 0.5 mph (26 kph +/- 0.8 kph)
STEERING & SUSPENSION		
Steering	Self-compensating Rack & Pinion	Self-compensating Rack & Pinion
Front Suspension	Leaf Springs w/ Hydraulic Shock Absorbers	Leaf Springs w/ Hydraulic Shock Absorbers
Rear Suspension	Leaf Springs w/ Hydraulic Shock Absorbers	Leaf Springs w/ Hydraulic Shock Absorbers
Service Brake	Rear Wheel Mechanical Self-adjusting Drum	Rear Wheel Mechanical Self-adjusting Drum
Parking Brake	Self-compensating, Single-point Engagement	Self-compensating, Single-point Engagement
Front & Rear Tires	Links 18 x 8.5 - 8 (4 Ply Rated)	Links 18 x 8.5 - 8 (4 Ply Rated)
FRAME & COLOR		
Frame	Powder Coated Welded Steel	Powder Coated Welded Steel
Front Body & Finish	Injection Molded TPO	Injection Molded TPO
Rear Body & Finish	Steel. Base Coat/Clear Coat	Steel. Base Coat/Clear Coat
Standard Color	Patriot Blue	Patriot Blue

Options & Accessories

- Drop Side Rails
- Locking Glove Box
- Rear View Mirror
- Windshield
- Canopy
- Front Disc Brakes
- Pin Stripes
- Body Color (Hunter Green, Champagne or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Beacon Light Kit
- Dome and Work Lights
- Fuse Cab
- Steel Cab and Doors
- Defroster
- Wheel Covers - Spoke and Chrome
- Limited Slip Differential