

# SHUTTLE<sup>®</sup> 8



# EFFICIENT AND PRODUCTIVE HIGH VOLUME TRANSPORTATION.

The Cushman® Shuttle™ 8 is perfect for transporting large groups of people throughout any facility. With six forward-facing seats and two rear-facing seats, the Shuttle 8 can move up to eight people with ease. Choose between an energy-efficient 72V AC electric drivetrain or powerful 13.5 hp EFI gas engine. Features like a large canopy, ergonomically-designed seating, and dependable performance keep guests and workers happy.

13.5HP EFI GAS 72V AC ELECTRIC DRIVETRAIN P

8 PERSON SEATING CAPACITY

LET'S WORK.®





# **CUSHMAN**° SHUTTLE<sup>®</sup> 8

BODY & CHASSIS		
FRAME	Welded Steel w/ DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Patriot	Blue
DIMENSIONS		
OVERALL LENGTH	167.5 in (425 cm)	
OVERALL WIDTH	49.5 in (126 cm)	
OVERALL HEIGHT	45.5 in (116 cm) (w/o Roof) / 76.0 in (193 cm) (w/ Struts & Roof)	
WHEEL BASE	123.4 in (313 cm)	
WHEEL TRACK	36.0 in (91 cm) Front / 38.0 in (97 cm) Rear	
GROUND CLEARANCE	3.0 in (8 cm)	
CARGO DECK CAPACITY	400 lb (181 kg)	
POWER		
POWER SOURCE	72V DC	4-Cycle, 24.5 ci (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	22.4 hp (16.7 kW) Intermittent	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	72V	N/A
	Six, 12 Volt Deep Cycle	
BATTERY (QTY/TYPE)		Starter/Generator. Solid State Re
BATTERY CHARGER	1000 Watt, 72V, 120/230V VAC UL Listed	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replacable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	6 Gallon (22 L) Tank
SPEED CONTROLLER	350 Amp AC	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/	Helical Gears
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
REAR AXLE RATIO	17:1	11.47:1 (Forward) 14.35:1 (Revers
PERFORMANCE		
SEATING CAPACITY	8-Pei	rson
WEIGHT W/O BATTERIES	1203 lb (546 kg)	N/A
CURB WEIGHT	1695 lb (769 kg)	1265 lb (574 kg)
VEHICLE LOAD CAPACITY	1600 lb (	726 kg)
BED LOAD CAPACITY	400 lb (181 kg)	
OUTSIDE CLEARANCE CIRCLE	33 ft (10 m)	33 ft (10 m)
SPEED	16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) (High Speed) 12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed)	16 mph ± 0.5 mph (26 kph ± 0.8 k
STEERING & SUSPE	NSION	
STEERING	Self-Compensatir	ng Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	4-Wheel Hydraulic Brakes Front Disk, Rear Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
	con componicating, on	

# HEADLIGHTS



## OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pinstripes
- On Board Charger
- Body Color (Forest Green, White, Ivory, Black or Custom Options)
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
  - CE Kit (gas only)



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

## www.cushman.com

©2019 Textron Specialized Vehicles Inc. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.